

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
19 August 2004 (19.08.2004)

PCT

(10) International Publication Number
WO 2004/068990 A1

(51) International Patent Classification⁷: A44C 5/00, 5/12

(21) International Application Number:
PCT/GB2004/000468

(22) International Filing Date: 6 February 2004 (06.02.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0302690.3 6 February 2003 (06.02.2003) GB

(71) Applicant (for all designated States except US): SNAP-
WATCH LIMITED [GB/GB]; Corner Cottage, Monxton,
Hampshire SP11 8AH (GB).

(72) Inventor; and

(75) Inventor/Applicant (for US only): DOUGLAS, Vincent
[GB/GB]; Corner Cottage, Monxton, Hampshire SP11
8AH (GB).

(74) Agent: MURGITROYD & COMPANY; Scotland
House, 165-169 Scotland Street, Glasgow G5 8PL (GB).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.


(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), Euro-
pean (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR,
GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK,
TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW,
ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: DISPLAY APPARATUS



(57) Abstract: A display apparatus (10) comprises a display band (14) and a control unit (12). The display band (14) is flexible and is dimension for wrapping round the wrist or other part of the user. In preferred forms, the control unit (12) includes a timing circuit and the display band (14) includes a digital time display, the apparatus thus functioning as a watch. Also preferred is the use of a malleable display band (14) allowing the apparatus to be applied to the wrist or the like without use of a buckle or catch. A variety of display bands (14) may be used interchangeably with a single control unit

WO 2004/068990 A1

1 Display Apparatus

2

3 The present invention relates to display apparatus,
4 particularly, but not exclusively, display apparatus
5 which is used as personal jewellery or wrist
6 watches.

7

8 Most people own a wristwatch and they can be found
9 in a number of guises to suit personal taste and
10 disposable income. They all have the same basic
11 features, however, of a central section which
12 provides the time and display (be it analogue or
13 digital) and also contains the watch's mechanism, a
14 strap or bracelet which surrounds the wearer's wrist
15 and a clasp or buckle to secure the whole
16 arrangement to the wearer's wrist.

17

18 The present invention is directed to a display
19 apparatus for personal wear.

20

1 The present invention provides a display apparatus
2 comprising a flexible display member and a control
3 unit provided at one end of the display member, the
4 display member being in the form of a strip of a
5 size suitable to be positioned around a limb of a
6 user.

7

8 In one form of the invention, the display member is
9 malleable, the malleable display member preferably
10 being sufficiently stiff as to retain its shape
11 without the need for a latch or other retainer.
12 This allows a given product to fit a wide range of
13 users, and makes the product easier to use.

14

15 The term "malleable" is used herein to mean capable
16 of being shaped or moulded by the application of
17 hand pressure to a shape which is retained until the
18 shape is again altered by hand pressure. One form
19 of malleable member contemplated in this invention
20 is a strip or band of thin metal or plastic and
21 which is initially axially straight and transversely
22 concave. An alternative is to use a strip or band
23 of a low yield point, such as a soft alloy.

24

25 The display member may comprise an electro-
26 luminescent display bonded to a malleable strip; and
27 in a preferred form the display member comprises a
28 rubber backing, a strip of thin steel forming said
29 malleable strip, said electro-luminescent display, a
30 filter layer, and an anti-moisture covering.

31

1 In an alternative form of the invention, the
2 apparatus can be secured by a buckle or clasp.

3

4 In either form, controls are preferably provided on
5 the display member, most suitably in the form of
6 touch-sensitive areas on the display. This
7 simplifies construction, and makes it easier to seal
8 the apparatus against water.

9

10 The control unit preferably comprises a timing
11 circuit and the display member is adapted to display
12 time indicia, whereby the apparatus functions as a
13 watch. Additionally, or alternatively, the control
14 unit may comprise means for generating visual
15 patterns on the display member, whereby the
16 apparatus functions as an electronic bracelet.

17

18 Preferably also, the display member is removably
19 attached to the control unit, whereby the display
20 member can be detached and replaced with an
21 alternative design or size to suit the individual.
22 Thus, the apparatus can readily be adapted to
23 different styles and appearances according to the
24 desires of the user and his/her social milieu at a
25 given time.

26

27 An embodiment of the present invention will now be
28 described, by way of example only, with reference to
29 the accompanying drawings in which:

30

31

1 Fig. 1 is a plan view of a display apparatus
2 according to the present invention;

3
4 Fig. 2 is a perspective view of the apparatus
5 of Fig. 1 in which the apparatus has been
6 moulded into a loop;

7
8 Fig. 3 is a perspective view of the apparatus
9 of Fig.1 showing the details of the
10 construction of the apparatus;

11
12 Fig. 3a is a cross-section of part of Fig. 3 to
13 an enlarged scale; and

14
15 Fig. 4 is a schematic of an alternative circuit
16 arrangement.

17
18 Referring to the drawings and initially to Fig. 1
19 there is shown a watch according to the present
20 invention generally referred to as 10. The watch 10
21 comprises two main elements, a control unit 12 and a
22 malleable display band or sprung band 14. The
23 control unit 12 and the sprung band 14 are not
24 permanently connected and can be readily
25 interchanged.

26
27 The control unit 12 contains all of the required
28 mechanisms and the power source for the watch. It
29 consists of a rear cover 26 and a top cover 28 which
30 clip securely together and house a battery 12a and
31 electronics 12b.

32

1 In this case the watch uses a standard quartz
2 circuit and an ordinary watch battery.

3

4 The sprung band 14 is constructed from several
5 layers which are shown in greater detail in Fig. 3,
6 and which are held together by double-sided LSE
7 clear 3M adhesive between adjacent layers.

8

9 The bottom layer 16 is a 500µm thick natural rubber
10 section. Above that is a layer 18 composed of a
11 50µm plastic coated hardened and tempered steel.
12 Above that is a 100µm thick electro-luminescent
13 display layer 20 on top of which is a 50µm polyester
14 deep dyed filter layer 22. Finally, there is a
15 100µm anti-moisture ingress coating 24. All five
16 layers form a composite sandwich to make up the
17 sprung band 14.

18

19 The steel layer 18 has the transverse shape shown in
20 Fig. 3a, that is curved in a gentle arc, when the
21 sprung band 14 extends in a straight path. When the
22 apparatus is applied to the wrist and wrapped around
23 it, the transverse curve straightens out and the
24 tension in the layer 18 acts to maintain the band in
25 its wrapped condition until peeled off.

26

27 The four layers apart from the electroluminescent
28 layer 20 terminate first inside the control unit 12.
29 The electroluminescent layer 20 continues further
30 into the control unit 12 and adopts its shape. The
31 layer 20 has a beryllium-copper surface-mounted
32 connector similar to the mounting of an LCD in a

1 mobile phone. This allows the user to have several
2 displays of differing colours and layouts driven
3 from a common driver circuit and battery.

4

5 The sprung band 14 also contains touch sensitive
6 buttons (not shown). These are used to control the
7 functions of the watch such as setting the time.
8 Buttons may also be included which alter the display
9 properties of the band, for example to increase
10 luminescence or to change a decorative pattern on
11 the watch.

12

13 It will be appreciated that the display must be
14 flexible. In addition to electroluminescent
15 displays, other forms of flexible display may be
16 used such as organic light emitting diode, light
17 emitting polymer, and organic liquid crystal
18 display.

19

20 In use the watch 10 is placed over the wearer's
21 wrist in its initial flat form. The wearer then
22 applies pressure to the ends of the watch 10. The
23 sprung band 14 yields to the pressure and moulds
24 around the wearer's wrist as described above. Once
25 a desired fit is attained, the wearer discontinues
26 the application of pressure. The watch 10 is left
27 in a moulded position around the wearer's wrist.
28 The watch 10 in this form can be seen more clearly
29 in Fig. 2.

30

31 The watch 10 does not require any latch mechanism to
32 hold it in this position, as the malleability of the

1 sprung display band 14 retains it around the
2 wearer's wrist until the wearer wishes to remove it.

3

4 Since the watch 10 has a malleable property, it can
5 be readily moulded into a number of shapes or sizes.

6 Standard lengths of display bands 14 can fit a
7 variety of wearers with differing wrist sizes.

8 Alternatively a single wearer can deploy the watch
9 on another limb; the leg for example.

10

11 Since the control unit 12 and display band 14 are
12 interchangeable, the wearer can alternate shapes and
13 designs of display band to suit mood or occasion.

14

15 Figure 4 illustrates a more sophisticated control
16 arrangement. In Figure 4, a display 40 is
17 controlled by a microprocessor 42 via a display
18 driver circuit 44. For use as a watch, accurate
19 time reference is given by a reference crystal 46.
20 Control inputs to the microprocessor 42 are provided
21 by touch-sensitive inputs 48. The apparatus is
22 powered by a battery 50, which is preferably a
23 rechargeable battery (most suitably using lithium
24 ion technology) which can be recharged via power
25 inputs 52, or by an inductive arrangement. For
26 example, recharging could be by an existing cell
27 phone charger via a suitable adaptor.

28

29 Alternatively, the battery may be recharged by a
30 solar cell or by a thermoelectric cell using the
31 body heat of the wearer.

32

1 As a further alternative, a lithium ion polymer
2 battery could be used; since these are conformable,
3 the battery could be included in the wrists trap
4 rather than the control unit.

5

6 Power consumption may be reduced by providing a
7 light sensor and controlling the display
8 illumination in accordance with ambient light.

9

10 The example of Figure 4 is suited for use where the
11 display 40 is in the form of a pixel array. In this
12 case, the display can be controlled to display the
13 time together with fixed or dynamic graphics, which
14 may be pictorial or abstract, and monochrome or
15 colour. Also, since the arrangement of Figure 4 is
16 microprocessor based, it would be simple to include
17 a radio frequency link, for example using Bluetooth
18 technology, and to use the control inputs 48 for
19 remote control of other devices.

20

21 A number of modifications are envisaged without
22 departing from the scope of the invention.

23

24 The invention may be provided as an item of
25 adornment only, not containing a time displaying
26 function. The invention could therefore display an
27 attractive design for aesthetic purposes only. This
28 design could also be changeable via the control unit
29 alternating between several designs.

30

31 The invention may include means to program the
32 device to alternate the displayed design at a set

1 frequency, or to strobe or produce other interesting
2 or eye-catching effects.

3

4 All this can be separate from or in conjunction with
5 a display of the time.

6

7 The apparatus may be double sided, such that it can
8 be wrapped around the wrist in either direction.

9 One side might then display the time and the other
10 side a graphic display. Either side or both may be
11 animated.

12

13 The apparatus may include an external plastic casing
14 enclosing the whole apparatus.

15

16 Furthermore, the invention may include a sound
17 sensor linked to the display feature. Therefore if
18 the invention is exposed to a sound source, for
19 example if the wearer is in a nightclub, the
20 invention would provide an attractive display which
21 flashes or illuminates selectively in response to
22 the tempo of the music.

23

24 Although it is preferred to have the display band
25 readily detachable from the control unit, it would
26 be possible to mount the control circuitry directly
27 onto the display substrate, possibly but not
28 necessarily a rigid portion.

1 CLAIMS

2

3 1. A display apparatus comprising a flexible
4 display member and a control unit provided at one
5 end of the display member, the display member being
6 in the form of a strip of a size suitable to be
7 positioned around a limb of a user.

8

9 2. A display apparatus according to claim 1, in
10 which the display member is malleable.

11

12 3. A display apparatus according to claim 2, in
13 which the malleable display member is sufficiently
14 stiff as to retain its shape without the need for a
15 latch or other retainer.

16

17 4. A display apparatus according to claim 3, in
18 which the malleable display member is a strip or
19 band of thin metal or plastic and which is initially
20 axially straight and transversely concave.

21

22 5. A display apparatus according to any of claims
23 2 to 4, in which the display member comprises an
24 electro-luminescent display bonded to a malleable
25 strip.

26

27 6. A display apparatus according to claim 5, in
28 which the display member comprises a rubber backing,
29 a strip of thin steel forming said malleable strip,
30 said electro-luminescent display, a filter layer,
31 and an anti-moisture covering.

32

1 7. A display apparatus according to claim 1, in
2 which the control unit can be secured to a distal
3 portion of the display member by a buckle or clasp.
4

5 8. A display apparatus according to any preceding
6 claim, in which controls are provided on the display
7 member.
8

9 9. A display apparatus according to claim 8, in
10 which said controls are in the form of touch-
11 sensitive areas on the display.
12

13 10. A display apparatus according to any preceding
14 claim, in which the control unit comprises a timing
15 circuit and the display member is adapted to display
16 time indicia, whereby the apparatus functions as a
17 watch.
18

19 11. A display apparatus according to any preceding
20 claim, in which the control unit comprises means for
21 generating visual patterns on the display member,
22 whereby the apparatus functions as an electronic
23 bracelet.
24

25 12. A display apparatus according to any preceding
26 claim, in which the display member is removably
27 attached to the control unit, whereby the display
28 member can be detached and replaced with an
29 alternative design or size to suit the individual.
30
31

1 / 4




Fig. 1

2 / 4







Fig. 2

3 / 4

*Fig. 3**Fig. 3a*

4 / 4

*Fig. 4*

INTERNATIONAL SEARCH REPORT

International Application No
PCT/GB 20/04000468

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 A44C5/00 A44C5/12

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 A44C

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 00 59327 A (TIME WARNER ENTERTAINM CO LP) 12 October 2000 (2000-10-12)	1,8-11
Y	page 3, line 19 -page 5, line 30; figures 1-10	2-7,12
Y	FR 2 670 092 A (CODINA)	2-6
A	12 June 1992 (1992-06-12)	
A	abstract; figures 1-6	1
Y	US 5 515 247 A (CHEUNG JACKY ET AL)	7,12
A	7 May 1996 (1996-05-07)	
A	column 2, line 35-45; figure 3	1
X	US 2001/008074 A1 (RADLEY-SMITH PHILIP J)	1
	19 July 2001 (2001-07-19)	
	abstract; figure 3	
	--- -/--	

☒ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

& document member of the same patent family

Date of the actual completion of the international search

10 May 2004

Date of mailing of the international search report

21/05/2004

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
 NL - 2280 HV Rijswijk
 Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
 Fax: (+31-70) 340-3016

Authorized officer

Janssens, G

INTERNATIONAL SEARCH REPORT

International Application No
PCT/GB 20/04000468

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	DE 40 29 223 A (STRIEBEL CHRISTHARD) 19 March 1992 (1992-03-19) column 2, line 35-42; figures 1,2	1,7,12

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/GB 20/04000468

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 0059327	A	12-10-2000	AU 4040000 A WO 0059327 A1	23-10-2000 12-10-2000
FR 2670092	A	12-06-1992	FR 2670092 A3	12-06-1992
US 5515247	A	07-05-1996	NONE	
US 2001008074	A1	19-07-2001	US 2003066308 A1 AT 253743 T AU 4395096 A DE 69630587 D1 EP 1215546 A1 EP 0803084 A1 GB 2297021 A ,B WO 9621888 A1 GB 2328139 A ,B HK 1011916 A1 HK 1018190 A1 US 6216490 B1	10-04-2003 15-11-2003 31-07-1996 11-12-2003 19-06-2002 29-10-1997 24-07-1996 18-07-1996 17-02-1999 19-05-2000 12-05-2000 17-04-2001
DE 4029223	A	19-03-1992	DE 4029223 A1	19-03-1992